


Freestanding Play  
(5-12 years)

TOTAL ELEVATED PLAY COMPONENTS	0	REQUIRED	0
TOTAL ELEVATED COMPONENTS ACCESSIBLE BY RAMP	0	REQUIRED	0
TOTAL ELEVATED COMPONENTS ACCESSIBLE BY TRANSFER	0	REQUIRED	0
TOTAL ACCESSIBLE GROUND LEVEL COMPONENTS SHOWN	1	REQUIRED	0
TOTAL DIFFERENT TYPES OF GROUND LEVEL COMPONENTS	1	REQUIRED	1



Design #3889

Landscape Structures

SYSTEM TYPE:  
Free Standing

DRAWING #:

The play components depicted on this plan are IPEMA certified. IPEMA model number is provided with the use and layout of components. Components are designed to meet requirements of ASTM F1487 for safety product certification. Visit www.landscape.com

---

THIS PLAY AREA & PLAY EQUIPMENT IS DESIGNED FOR A LIFE OF 15 YEARS UNLESS OTHERWISE NOTED ON PLAN.

---

IF BY THE MANUFACTURER'S OPINION THAT THIS PLAY AREA DOES CONFORM TO THE AIAA ACCESSIBILITY STANDARDS, ASSUMING AN ACCESSIBLE PROTECTIVE SURFACING IS PROVIDED AS INDICATED, OR WITHIN THE ENTIRE USE ZONE.

---

THIS CONCEPT PLAN WAS BASED ON INFORMATION AVAILABLE TO US AT THE TIME OF CONSTRUCTION. OBTAIN THE MANUFACTURER'S, INCLUDING THE DIMENSIONS, PERFORMANCE, DESIGN SOLUTIONS SHOULD BE OBTAINED. AVOIDANCE OF PLAY AREA, SIZE, ORIENTATION, THE LOCATION OF ALL EXISTING UTILITIES, EQUIPMENT AND THE SURFACING AREA OF PLAYERS. THIS SHOULD NOT FACE THE SUN AT ANGLE OF 90°.

---

CHOOSE A PROTECTIVE SURFACING MATERIAL THAT HAS A MINIMUM HEIGHT TO MEET THE MANUFACTURER'S FALL HEIGHT FOR THE EQUIPMENT. FOR A FALL HEIGHT OF 10 FEET OR MORE, CONSIDER SAFETY PERFORMANCE SPECIFICATION FOR AN ANTI-COLLAPSE SURFACING. FOR A FALL HEIGHT OF 5 FEET OR LESS, CONSIDER A SAFETY SURFACING. THE SURFACING SHOULD BE WELL DRAINED IF THE SOIL DOES NOT DRAIN NATURALLY. IT MUST BE 1/4" TO 1/2" DEEP, 1/4" TO 1/2" HIGH TO A STORM SEWER OR A TRENCH DRAIN.

---

DESIGNED BY:

COPYRIGHT 5/7/14  
LANDSCAPE STRUCTURES, INC.  
401 7th STREET SOUTH - P.O. BOX 100  
DUNWOODY, GEORGIA 30328-1100

DATE	PROJECT	DRAWING



